

999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Slot-In !



- Slim type Slot Loading design
- Buffer underrun Prevention
- Supporting disc-at-once, session-at-once, packet write, incremental, over write, track-at-once recording mode, sequential write, multi-session, and back ground format
- Horizontal and vertical mounting for most system configuration
- Emergency Eject Function

**Write Speed**

- DVD+R 8x ( ZCLV ), 3x ( CLV )
- DVD+R DL 6x ( ZCLV ), 3x ( CLV )
- DVD-R 8x ( ZCLV ), 3x ( CLV )
- DVD-R DL 6x ( ZCLV ), 3x ( CLV )
- DVD+RW 8x ( ZCLV ), 3x ( CLV )
- DVD-RW 6x ( ZCLV ), 3x ( CLV )
- DVD-RAM 5x ( P-CAV ), 3x ( CLV ), 2x ( CLV )
- CD-R 24x ( ZCLV ), 10x ( CLV )
- CD-RW US+ 16x ( ZCLV ), 10x ( CLV )
- US 24x ( ZCLV ), 10x ( CLV )
- HS 10x ( CLV )
- MS 4x ( CLV )

**Read Speed**

DVD-ROM 8x ( CAV )  
DVD±R 8x ( CAV )  
DVD±R DL ( Finalized Disc ) 8x ( CAV )  
DVD-RAM ( 4.7G ) 5x ( CAV )  
CD-ROM 24x ( CAV )  
CD-R 24x ( CAV )  
CD-RW 24x ( CAV )  
CD-DA ( DAE ) 24x ( CAV )

Disc Diameter 12cm, 8cm  
Interface SerialATA Revision 2.6  
Data Transfer Rate Gen1 1.5GB/sec  
Access Time 130ms ( typ ) DVD-ROM, 130ms ( typ ) CD-ROM  
Data Buffer 2MB  
Loading Mechanism Slot Loading Type

**Scope of supply:**

- Teac DV-W28SS drive
- SlimSATA-to-SATA Adapter