




134.00 EUR
incl. 19% VAT, plus [shipping](#)

- VIA VX900H Chipset
- Support VIA Nano L2007 (65nm,FSB 800MHz,1.6GHz) processor
- Integrated Chrome9 HD DX9 Engine
- Integrated LVDS support 24-bit TFT LCD
- Support 1 x PCIe x 16 slot (x 8 card)
- Support Serial ATA 2 Devices
- 1 * Gigabit LAN
- Support DC Fan
- VIA VT1705 HD Audio Codec with 6-Channel
- 170 x 170mm Mini-ITX Form Factor
- Support Watch dog Technology
- **CPU**
 - Support VIA Nano L2007 (65nm, 1.6GHz)processor
 - Front Side Bus 800MHz
- **Chipset**
 - VIA VX900H Chipsets
 - VIA Chrome9 HD DX9 3D engines (Share System Memory: 64/128/256/512MB)
- **Memory**
 - 2 * 240-pin DIMM Sockets for un-buffered DDR3 1066MHz SDRAM up to 8GB
- **Expansion Slots**
 - 1 * PCIe x 16 slot (x 8 card)
- **Power Management**
 - ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature

- | | |
|--|--|
| <ul style="list-style-type: none"> • Storage • Audio • Ethernet LAN • USB • LVDS • Rear Panel I / O • Internal I / O • BIOS • Form Factor • Packing • Certificate • Functional • Temperature | <ul style="list-style-type: none"> • 2 * Serial ATA2 3Gb/s connectors with RAID 0,1 function • 1 * Mini PCI-E • VIA VT1705 HD Audio Code with 6-Channel • 1 * RTL8111E 10 / 100 / 1000 PCI-E LAN • Embedded 7 * USB 2.0/1.1 • Each of onboard 24-bit Dual & Single channel LVDS connector • • 4 * USB 2.0/1.1 ports • 1 * RJ-45 port & 1 * SPDIF out • 3 * Audio I/O ports (Line-in, Mic and Line-out) • 1 * VGA port • 1 * DB-9 RS232 COM port • 1 * HDMI Connector • 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors • 2 * USB 2.0/1.1 headers for 3 USB ports • 1 * 9-Pin COM Port header (RS232/422/485) • 1 * 24 bit Dual Channel & 1 * 24 bit Single Channel LVDS header • 1 * Parallel header • 1 * GPIO header • 1 * 24-pin ATX power connector • AMI 8MB DIP-SPI Flash ROM • Mini-ITX Embedded Motherboard(170mmx170mm) • Color Box Dimension ■200(W) x 200(D) x 70(H)mm • 20 PCS in Cases Gross Weight ■15.4KGS • 20 PCS Net Weight ■10.3KGS • 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm • CE,FCC,RoHS • ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation • Operating within 0~60 centigrade • Storage within -20-85 centigrade |
|--|--|

Product Accessories

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield