




1019.00 EUR  
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- AMD RS785 Chipset + SB750 Chipset
- Support Socket AM2+ Quad core Opteron™ & Phenom™
- Support HT3.0 Technology
- Integrated ATI Radeon HD 4200(Support Microsoft DX 10.1)
- Support 4 Serial ATA2 Devices with RAID 0,1,5,10
- Support Dual Channel DDR2 800/667
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support DVI-D/HDMI Output
- Supports 10/100M LAN / Gigabit LAN
- Compliance with EuP standard
- Support CPU Smart FAN
- Ready for Windows® 7™
- ITX Form Factor(170mm x 170mm)
- CPU
- Chipset
- Memory
- Expansion Slots
- Support AMD Socket AM2/AM2+
- AMD RS785 Chipset + SB750 Chipset
- 2 \* SODIMM Sockets for un-buffered Dual Channel DDR2 800 SDRAM up to 4 GB
- 1 \* 32-bit PCI slot
- 1 \*MINI PCI-E Connector

- Storage
- Audio
- Ethernet LAN
- USB
- Special Features
- Rear Panel I / O
- Internal I / O
- Functional
- Temperature
- BIOS
- Form Factor

**Embedded SB750 Chipset**

- 4 \* Serial ATA2 3Gb/s connectors
- Supports HDDs with RAID 0, 1,5,10 functions
- Realtek ALC662 6-Channel HD Audio CODEC
- Realtek RTL8111DL PCI-E LAN chip for 10/100M LAN / Gigabit LAN
- Embedded 10 \* USB 2.0/1.1
- Advanced Power Design that supports the latest Socket-AM2+ CPU
- "IMAGE IT!" System Backup Software and "ProMagicPLUS!" System Recovery System
- 6 \* USB 2.0/1.1 ports
- 1 \* PS2 KB/MS port
- 1 \* RJ-45 port & 2 \* e-SATA ports
- 1 \* Audio I / O ports
- 1 \* VGA port
- 1 \* DVI-D port
- 1 \* HDMI port
- 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
- CPU / Chassis Fan connectors;
- 1 \* 4-pin ATX 12V Power connector
- 1 \* 20-pin ATX Power connector
- 1 \* COM header
- ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
- Operating within 0~50 centigrade
- Storage within -20-85 centigrade
- 8MB SPI Flash ROM
- Mini ITX Form Factor(17cmx17cm)

**Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield