



249.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- NVIDIA 610M GPU !
- 5x SATA !



- INTEL® Cedar Trail-D Processor D2550 + ICH10R Chipset + NVIDIA® 610M GPU
- Support 2 \* DDR3 1066MHz Single CH up to 8GB
- Support DirectX 11 Graphics up to 850MHz
- 5 ports Serial ATAII (3Gb/s) with RAID 0, 1, 5,10 supported
- Realtek ALC887 8-CH HD Audio CODEC
- Support HDMI, DP & DVI-I (Dual Link) Display output
- Supports 1 \* Realtek RT8111F Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

<b>CPU</b>	• INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz)
<b>Chipset</b>	• INTEL® ICH10R Express chipset
<b>GPU</b>	• Nvidia 610M
<b>Memory</b>	• 2 * DDR3 1066/800MHz Single CH SO-DIMM up to 8GB
<b>Expansion Slots</b>	• 1 * MINI PCI-E
<b>Storage</b>	• 5 * Serial ATAII 3Gb/s with RAID 0,1, 5, 10 supported • 1 * mSATA (Selectable with Mini PCI-E)
<b>Audio</b>	• Realtek ALC887 8-CH HD Audio CODEC

• <b>Ethernet LAN</b>	• 1 * RTL8111F PCI-E Gigabit LAN
• <b>USB</b>	• Embedded 8 * USB 2.0/1.1
• <b>Special Features</b>	• Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog
• <b>Rear Panel I/O</b>	• 4 * USB 2.0/1.1 ports • 1 * RJ-45 port • 2 * COM ports • 1 * DP port • 1 * HDMI port • 1 * DVI-I (Dual Link) port • 1 * Audio I/O port • 1 * +12V DC-in jack
• <b>Internal I/O</b>	• 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports • CPU /NB / Chassis Fan connectors; • 1 * GPIO header • 1 * TPM header • 1 * CIR • 1 * Chassis Intrusion header
• <b>BIOS</b>	• AMI 16MB UEFI DIP Flash ROM
• <b>Form Factor</b>	• Mini ITX Form Factor(170mm x 170mm)
• <b>Functional</b>	• POS, Digital Signage, Gaming Machine, Kiosk
• <b>Certificate</b>	• CE, FCC, RoHS
• <b>Temperature</b>	• Operating within 0~60 centigrade • Storage within -20-85 centigrade