



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Fanless !
- IP65 Front !
- POE !
- Android !

Support:  [Specifications](#)

- 10.1" 300 nits TFT LCD with LED backlight
- Onboard DDR3L 1333 2GB DRAM
- Onboard 8G Flash ROM
- Strong solid aluminum frame design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Front IP65 for protection against water and dust
- Front bezel meets IP65-rated protection
- Support PoE input
- Jetway also provides 13.3" and 15" Panel PC models, for other sizes please contact sales for more details

| Display                 |                                                     |
|-------------------------|-----------------------------------------------------|
| Front Bezel             | – IP65, NEMA 4 rugged protection, metal front bezel |
| Display Type            | – 10.1" With LED Backlight                          |
| Brightness (cd/m²)      | – 300 nits                                          |
| Display Color           | – 262K                                              |
| Resolution              | – 1920 x 1200 @ 60Hz                                |
| Viewing Angle (H/V)     | – 140°/140°                                         |
| Pixel Pitch             | – 0.03775 x 0.03775 mm                              |
| Aspect Ratio            | – 16:10                                             |
| Contrast Ratio          | – 500:1                                             |
| Response Time           | – 60 ms                                             |
| Touch Screen            |                                                     |
| Type                    | – projected capacitive type                         |
| Active Range            | – 257.10 x 159.66mm ±0.2mm                          |
| Transparency            | – ■87%                                              |
| Operating Force         | – ■50g                                              |
| Surface Hardness        | – ■6H (ASTM D3363, pressure 1N/45°))                |
| Operating Temperature   | – -10 ~ +60° C                                      |
| CASE                    |                                                     |
| Panel Material          | – Aluminum                                          |
| Case Material           | – Iron                                              |
| Color                   | – Black                                             |
| Coating Requirement     | – Spray Paint                                       |
| Main System             |                                                     |
| CPU                     | – Rock Chip® ARM Cortex A17 1.8GHz/QC               |
| RAM                     | – 2G DDR3L                                          |
| Flash ROM               | – 8G Flash ROM                                      |
| Watchdog Timer          | – 256 levels, 0~255 sec.                            |
| Speaker                 | – 2* 2W/8Ohm                                        |
| OS Support              | – Android 5.1                                       |
| I/O Connector           |                                                     |
| I/O Ports and Switches  | – 1* USB2.0<br>– 1* OTG<br>– 1* PoE PD              |
| PoE                     |                                                     |
| Regulatory Compliance   | – IEEE802.3af (PoE)                                 |
| Input Power             | – 44~57V                                            |
| Pass Through Data Rates | – 10/100/1000 Mbps                                  |
| Power Consumption       | – 8.5W                                              |
| Dimension               |                                                     |
| Case Dimensions         | – 259.3*177.3*34.5mm                                |
| Certifications          |                                                     |
| Certifications          | – CE, FCC, IP65(Front)-Option                       |
| Environment             |                                                     |

|                 |                                                                                                            |
|-----------------|------------------------------------------------------------------------------------------------------------|
| Temperature     | <ul style="list-style-type: none"> <li>– Operating: -10 ~ 50° C</li> <li>– Storage: -20 ~ 60° C</li> </ul> |
| Shock           | – Operating: 15G■11ms duration                                                                             |
| Vibration       | – Operating: 5~500Hz/1 Grms                                                                                |
| <b>Warranty</b> |                                                                                                            |
| Warranty        | – 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty )                                     |