



649.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel® BayTrail-M N2930 Quad Core Processor
- 2 * SO-DIMM DDR3L 1333MHz up to 8GB
- 2 x Gigabit LAN , 2 x Bypass Gigabit LAN , 4 x Expansion Card Gigabit LAN
- Form Factor : 430 x 251 x 44 mm
- AC 90~240V_200W FLEX Power

MB Model	– JNF9HB-2930 / Mini-ITX		
Part No	Standard	4 ports GbE PCI-E expansion card	2 Pairs of Bypass LAN expansion card
	– HBJC153F9HB-2930-B	– HBJC153F9HB-2930G4	– HBJC153F9HB-2930B4
BIOS	– AMI 64MB SMT Flash ROM		
CPU/Chipset	– Intel® Bay Trail-M N2930 SoC Processor (Default)		
Memory	Support 2 * DDR3L 1333/1066MHz SO-DIMM up to 8GB		
Storage	– Support 2 * 2.5" SATA Drive bay (only support 2.5" HDD with a height ≤ 10mm) – Support 1 * full-size mSATA/Mini-PCI Express shared slot		
Expansion	– 1 * full size Mini-PCle – 1 * SIM card slot – Support TPM (optional)		
Network	– 4 * Intel i211AT GbE (1 pair support ByPass GbE) – 1 * full-size Mini-PCle slot (802.11 b/g/n + BT 4.0 installed in WiFi model)		
Rear Panel I/O	– 1 * Power switch – AC input / 1U FLEX 200W Power build in		
Front Panel I/O	– 4 * RJ45 (1 pair support ByPass GbE) – 1 * USB3.0) – 1 * USB2.0) – 1 * VGA) – 2 * COM) – 1 * PW LED, 1 * Alarm LED) – 1 * GPIO (Not assembled when shipped, wire placed in the parts box)) – 4 ports GbE PCIe expansion card: HBJC153F9HB-2930G4) – 2 pairs of Bypass LAN PCIe expansion card: HBJC153F9HB-2930B4		
Power Source	– 1U FLEX 200W Power build in – AC 90~240V input		
Compliance	– CE, FCC, RoHS		
Temperature	– Operating temperature: 0 ~ 40° C – Storage Temperature: -10 ~ 70° C		
Dimensions	– 430 (W) x 252 (D) x 44 (H) mm		
Packing	– Net Weight: 4.2KG – Gross Weight: 5KG – Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm		

OS Support	– Windows 7, Windows 8.1, Windows 10, Linux
Warranty	– 2 Years limited warranty