



1159.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake-UP3 !
- 4x 4K HDR !
- 2x USB-C !
- WLAN !

**Support:** [Datasheet](#)

- Intel® Tiger Lake-UP3 SoC Processor (TDP 15W)
- 2\* DDR4 3200MHz SO-DIMM up to 64GB
- 2\* HDMI, 2\* DP1.4 (from Type-C), 1\* eDP, 1\* RS232, 3\* USB3.2 (Gen.2), 3\* USB2.0, 2\* USB3.2 (Gen. 2) Type-C support DP1.4 display output
- Support Four independent 4K HDR Display
- DC 12V 90W Adapter

MB Model	– MF10-20 (i5-1145G7E / Default) – MF10-22 (i5-1145G7E / TPM2.0) – MF10-90 (i5-1135G7) – MF10-92 (i5-1135G7 / TPM2.0)	
Part No	Non-Wifi	M.2 ac WiFi card
	– HBFDF10-45G7-B (Default) – HBFDF10-45G7-T – HBFDF10-35G7-B	– HBFDF10i-45G7-B (Default) – HBFDF10i-45G7-T – HBFDF10i-35G7-B – HBFDF10i-35G7-T
Processor	– Intel® Tiger Lake-UP3 SoC Processor (TDP 15W), Default: 1145G7E	
Memory	– 2* DDR4 3200MHz SO-DIMM up to 64GB	
Storage	– 1* SATAIII (6Gb/s) – M.2 M-key 2242/2280, PCIe 4.0 x4/SATA interface, support NVMe	
Network	– 1* Intel i219-LM 1.0GbE – 1* Intel i225V 2.5GbE	
Expansion slot	– M.2 E-key (2230) USB2.0/PClex1 interface support CNVi – M.2 B-Key 3042/3052 (USB3.1/USB2.0/PCIe x1)	

Front Panel I/O	<ul style="list-style-type: none"> <li>- 1* Power button</li> <li>- 1* Reset button</li> <li>- 1* Power LED</li> <li>- 1* HDD LED</li> <li>- 2* USB2.0</li> </ul>
Rear Panel I/O	<ul style="list-style-type: none"> <li>- 3* USB3.2(Gen2)</li> <li>- 1* USB2.0</li> <li>- 2* USB3.2 (Gen.2) Type-C support DP1.4 display output</li> <li>- 2* RJ45</li> <li>- 2* HDMI</li> <li>- 1* Line-out/MIC Combo</li> <li>- 1* COM or GPIO (Option)</li> <li>- 3* Antenna holes (Option)</li> <li>- 1* DC-in</li> </ul>
Compliance	- CE, FCC, LVD, RoHS
Power Source	<ul style="list-style-type: none"> <li>- DC Adapter 90W</li> <li>- M/B: DC 12~24V input</li> </ul>
Safety	- CE, FCC, LVD, RoHS
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: -20 ~ 50° C (Under the condition of using M.2 interface SSD)</li> <li>- Operating Temperature: 0 ~ 50° C (Under the condition of using 2.5" SATA HDD)</li> </ul> <p>(The test environment is closed and windless)</p> <ul style="list-style-type: none"> <li>- Storage Temperature: -20 ~ 70° C</li> </ul> <p>Humidity: Between 40% and 60%, non-condensing</p>
Dimensions	- 193 (W) x 142.4 (D) x 62 (H) mm
Packing	<ul style="list-style-type: none"> <li>- Net Weight: 2.2KG</li> <li>- Gross Weight: 3.2KG</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>
OS Support	- Windows 10, Linux