



899.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- 2x LAN !
- 6x USB !
- HAILO-8 Card !

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 6* USB, 2* RJ45, 1* Audio (MIC + Line-out), 1* Line-IN, 3* DP, 2*COM, 1* GPIO
- Support TPM2.0
- 160.2*106*43.5 mm
- Hailo-8 M.2 M key module inside, up to 26 TOPS
- DC12V_60W Adapter

Model	– HB368F21-6412-AI (EMMC,TPM)	
CPU/Chipset	– Intel® Elkhart Lake SoC Processor (J6412 , TDP 10W)	
BIOS	– AMI Flash ROM	
Memory	– 1* DDR4 3200MHz SO-DIMM up to 32GB	
Network	– 2* Realtek RTL8119I GbE	
Graphics	– Intel® HD Graphics, shared memory – 3* DP (Max Resolution: 4096×2160@60Hz) , Support Triple Displays	
Storage	– 64GB eMMC onboard	
Expansion	– 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) – 1* M.2 B-key (3042,USB3.0 interface)	
AI Accelerator	– 1* Hailo-8 M.2 M KEY module inside – 26 TOPS	
Rear Panel I/O	– 2* RJ45 – 2* USB3.1(Gen.2) – 1* USB2.0 – 1* 8 bit GPIO (Phoenix Connector 2*9 PIN) – 2* RS232/422/485 (Phoenix Connector 2*9 PIN) – 1* DC in (Lockable)	

Front Panel I/O	– 1* Power button + Power LED – 4* USB2.0 – 1* Audio(Line out+MIC) – 1* Line in – 3* DP
Internal Connector	– SIM Card Holder
Power Source	– Adapter : AC 90~240V input / DC12V_60W output – MB : DC12~36V input
Compliance	– CE, FCC, LVD, RoHS, ErP
Dimensions	– System: 160.2 (W) x 106 (D) x 43.5 (H) mm – Box: 250 (W) x 118 (D) x 295 (H) mm – Net Weight: 1.01KG – Gross Weight: 1.52KG
Temperature	– Operating Temperature: -20 ~ 70° C – Storage Temperature: -40 ~ 85° C – Humidity: 10% ~ 95% RH @40°C (non-condensing)
OS Support	– Windows 11, Linux