



329.95 EUR incl. 19% VAT, plus <u>shipping</u>

- STMF103VCT6 !
- RS-485 Communication !
- Ds1307 RTC !
- OLED Display !

- OLED Display 0.96'
- 14x Sink/Source Digital Inputs
- 10x 2A Relay outputs
- 2x NPN Transistor outputs
- 1x RS-485 Communication
- 2x Analog inputs 4-20mA
- 2x Analog inputs 0-10V DC

NORVI Arita is a higher capacity version of NORVI Series. Selection five standard models available with a choice two powerful micro-processors. Arita is designed to yield the every bit of performance in the micro-controller without compromising its reliability. It is compatible with almost every industrial input and output type. Connectivity is the factor which makes it suite today's world, for a connected world, we have included all the industrially accepted communication methods in it. Arita is used everywhere, it has many characters, it can be a motion controller handling heavy positioning tasks or a data logging server.

Main	
Range of product	NORVIARITA
Product type	Programmable Controller
Rated supply voltage	24V DC



Discrete input number	14 discrete input, interrupts configurable on each input
Analog input number	2x 4-20mA and 2x 0-10V DC
Discrete output type	Relay and Transistor
Discrete output number	10 Relay outputs, 2 Transistor outputs
Discrete output voltage	24V DC for transistor output
	0.5A with 10.0 10.1 Transistor
Discrete output current	2 A with R0R4 and Q0Q4 Relay outputs
Display	OLED Display 0.96'
Complementary	
Discrete IO number	26
Number of Expansions	4
Supply voltage limits	
Inrush current	<=50A
Power consumption in W	32.640.4 with all outputs ON
Discrete logic input	Sink or source
Discrete input voltage	24V
Discrete input voltage type	
Voltage state 1 guaranteed	>=15 V for input
Voltage state 0 guaranteed	<=5 V for input
Discrete input current	5 mA for input
Input impedance	4.7k Ohm for input
Memory capacity	Refer datasheet of base micro-controller
Battery type	lithium non rechargable *Model 8 Only
Backup time	2 years at 25'C *Model 8 Only
Local signalling	1 LED green for PWR
	1 LED green for RUN
	14 LED green for I0I14
	10 LED green for Q0Q4 and R0R4
	2 LED green for T0T1
Electrical connection	Removable screw terminal block for inputs and outputs (pitch 5.08 mm)
	Top hat type TH35-15 rail conforming to IEC 60715
Mounting support	Top hat type TH35-7.5 rail conforming to IEC 60715
	Plate or panel with fixing kit
Height	86.60 mm
Depth	56.60 mm
Width	122.10 mm
Product weight	0.43 Kg
Environment	
Resistance to electrostatic discharge	4kV on contact
	8kV on air
	10 V/m (80 MHz 1GHz)
Resistance to electro magnetic fields	3 V/m (1.4 MHz 2 GHz)
	1 V/m (2 MHz 3 GHz)
Immunity to microbreaks	10 ms
-	
Relative humidity	1095% without condensation in operation
IP degree of protection	P20
Operating altitude	02000m
Storage altitude	03000m
Shock resistance	15 gn for 11 ms