

0.00 EUR

incl. 19% VAT, plus [shipping](#)

- NVidia Jetson Orin NX !
- 16GB RAM !
- 4 x GMSL-2 / Model M12 !



- NVIDIA® Jetson Orin™ NX SoM with 1024 CUDA Cores
- 4 x GMSL Cameras Support
- 2 x Ethernet with M12 Connectors
- 1 x CAN FD for Vehicle Connection
- 9-60VDC Input with Built-in Smart Power Management
- -25°C ~ 70°C Operating with Fanless Design
- Watchdog for System Monitoring

#### System

#### IBOX-601-G2-01-ONX16

NVIDIA® Jetson Orin™ NX 16GB / VDB-101 / 4 x GMSL-2 / Model M12

#### Module

NVIDIA® Jetson Orin™ NX 16GB

(1024 CUDA cores + 8-core ARM Cortex-A78AE CPU + 16 GB LPDDR5)

#### Security

Platform Security Controller (PSC), Security Engine (SE)

|                          |   |                                                                                                                                                                                                                                                                                                            |
|--------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |   | <ul style="list-style-type: none"> <li>- 2 x M12 X-coded for 1 x 2.5GbE &amp; 1 x GbE<br/>( Intel® 2.5GbE, SoM Built-in GbE)</li> </ul>                                                                                                                                                                    |
|                          |   | <ul style="list-style-type: none"> <li>- 2 x USB 3.2 Type-A</li> <li>* Two ports share 10Gbps bandwidth</li> </ul>                                                                                                                                                                                         |
|                          |   | <ul style="list-style-type: none"> <li>- 1 x HDMI Type-A output supports 4K resolution</li> </ul>                                                                                                                                                                                                          |
|                          |   | <ul style="list-style-type: none"> <li>- 1 x HD Audio from the HDMI</li> </ul>                                                                                                                                                                                                                             |
| Interface                |   | <ul style="list-style-type: none"> <li>- 1 x DB-9 for RS-232/422/485</li> <li>- 4 x FAKRA for GMSL-2 cameras</li> <li>- 1 x DB-9 for CAN FD</li> <li>- 1 x USB Type-C for system recovery (Device only)</li> <li>- 1 x Nano SIM card slot</li> <li>- 5 x Pre-cut holes for external SMA antenna</li> </ul> |
| INTERNAL EXPANSION       | • | <ul style="list-style-type: none"> <li>1 x M.2 2230 Key E slot</li> <li>• 1 x M.2 3042/52 Key B slot (USB3.0) with nano SIM card slot</li> <li>• 1 x mPCIe full-size slot (USB.2.0 supported)</li> </ul>                                                                                                   |
| STORAGE (Internal)       | • | <ul style="list-style-type: none"> <li>1 x M.2 2280 Key M slot supports NVMe SSD (Pre-installed system BSP)</li> </ul>                                                                                                                                                                                     |
| Operating System / SDK   |   | <p>NVIDIA® JetPack including Jetson Linux, NVIDIA® development tools</p> <p>-25°C ~ 70°C (-13°F ~ 158°F), ambient w/ 0.6m/s airflow</p> <p>*Operating temp. varies by accessories installed.</p>                                                                                                           |
| Operating Temp.          |   | <p>-40°C ~ 80°C (-40°F ~ 176°F)</p>                                                                                                                                                                                                                                                                        |
| Storage Temp.            |   | <p>10% RH – 90% RH (non-condensing)</p>                                                                                                                                                                                                                                                                    |
| Relative Humidity        |   | <p>CE, FCC Part-15 Class A, E-mark, EN50155, EN45545-2 (R25)</p>                                                                                                                                                                                                                                           |
| Certification / Standard | • | <p>Random – IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis</p> <ul style="list-style-type: none"> <li>• MIL-STD-810G – Method 514.6, Procedure I, Category 4</li> </ul>                                                                                                                                     |
| Vibration                |   | <p>MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD</p>                                                                                                                                                                                                               |
| Shock                    |   | <ul style="list-style-type: none"> <li>• 1 x M12 K-coded for DC-IN 9 ~ 60V</li> </ul>                                                                                                                                                                                                                      |
| Power Input              |   | <ul style="list-style-type: none"> <li>• Supports Smart Power Management, OCP and OVP</li> </ul>                                                                                                                                                                                                           |
|                          |   | <p>Aluminum Alloy</p>                                                                                                                                                                                                                                                                                      |
|                          |   | <p>Fanless Passive Cooling Design</p>                                                                                                                                                                                                                                                                      |
| Mechanical               |   | <p>DIN-Rail, Wall Mount</p> <p>1770 g</p> <p>150 mm (L) x 135 mm (W) x 77 mm (H)</p>                                                                                                                                                                                                                       |

**Wi-Fi: M.2 2230 Wi-Fi Module**

**WWAN Modem: M.2 3042/52 WWAN Modem**

**GPS: mPCIe GPS Module**

**UPS: BAT-2300v2**

**Optional Accessories**

**GMSL Camera:**

**2MP 63.9° - Sony IMX390 2MP, 63.9°, GMSL-2**

**2MP 120.6° - Sony IMX390 2MP, 120.6°, GMSL-2**

**2MP 186.0° - Sony IMX390 2MP, 186.0°, GMSL-2**